

Ideal Imaging Solution

Developed for the Corporate Remote Deposit Capture market associated with financial transactions, the iS6100 provides a low cost viable check imaging solution without sacrificing image quality and scanner functionality. The compact size, and user friendly scanner are evident in the simple yet modern design.

Low Cost, Not Low Quality

iStream understands businesses want efficiencies at minimal cost. We've listened and developed a solution that won't break a business' pocket book, yet provides the benefits of a quality scanner.

The release of the iS6100 scanner provides a low volume solution enabling businesses of any size to leverage the benefits of remote deposit capture.

The iS6100 is a ideal scanner for a business that handles a small number of checks a day. The user simply places the check in the tray face down and hits the scan button. That's it!



Features & Benefits:

- **Easy to Install** - Simply plug in the USB 2.0 cable, the power cable and turn the scanner on.
- **Easy to Use** - Insert the check face down for a single pass dual sided imaging and stamping of the check.
- **Rapid Scanning Speed** - Approximately 30 documents a minute (1.5 seconds for a six inch document).
- **Compact Size** - Imager is oriented horizontally, with a small foot print.
- **Quality Images** - With JPEG grayscale image compression, your document images will look just as good as images from high end scanners. That means less hassle with bad images for you!
- **Durable Hardware** - Expect imager life is 7 years or 1 million of scans.
- **Check Stamp** - Ability to mark "imaged" on the front side of the check to identify it has been scanned.
- **Simple Maintenance** - Lift open the clam shell top to view and clean the scan path as necessary.
- **Additional Features**
 - Three-color LED for easy to understand status: On, Ready and Error in Scanning.
 - Unique scanner ID provides additional security.



iS6100 Series

Dimensions

Height	5.38" / (136.65mm)
Width	6.85" / (173.99 mm)
Length	11.3" / (287mm)
Orientation	Horizontal

Weight

Imager	2.2 Lbs. / (1.0 Kg.)
Ext. Power Supply	1.12 Lbs. Max. / (.051 kg)
Power Supply	24V Wall Mt, 3 Pin Mini Din Locking Connector

Form

Width	2" (50.8mm) MIN, 3.67" (93mm) MAX
Length	3.15" (80mm) MIN, 9.25" (235mm) MAX
Weight / Thickness	#16 up to 32# or 3.0 to 7.5 mils, .032"(81mm) for ID

Image Quality

Image Compression	8 Bit Grayscale @ 200DPI
Micr	24 Bit Color Option @ 200DPI
Sensors	200-400 DPI Option Monochrome
Indicators	CCITT G4 (Black / White) or JPEG (Grayscale).
Interface	In Line with Image Scanner
Memory	On- Board E13B Decoding Firmware
Speed	Form Insert, Jam & Skew
	Three Color Status LED -- Power On, Form Ready, Error
	High Speed Capable , USB 2.0
	32 MB DRAM upgrade able to 64MB

Processing Time	Single Pass Max 1.5 Seconds
Document Speed	10 Inches Per Second

OS Compatibility

Diagnostics	XP/2000/Vista
Maintenance	Command Based Self Test Feature
	General Periodic Cleaning takes less than 2 min and
	Can be performed by the operator.

Reliability

Life	Seven Years under normal usage/ 1 million scans
Warranty	2 Year Manufacturer

Environmental

Noise	58 dB
Operating	10° to 40° C, Humidity 10-85% Non-Condensing
Storage	-10° to 40° C, 10-85% Non-Condensing
Agency Listings	TUV CUE Conforms to EU CE, WEEE and RoHS directives
Emissions	FCC 15B Class A
Drivers	Windows XP, 2000, Vista

Options

- 24 Bit Color @ 200DPI Imaging
- 200-400 DPI Imaging Monochrome
- Unique ID for Security Purposes
- Form Stamp



**13555 Bishops Court
Suite 102
Brookfield, WI 53005
888-892-1212**

For additional information contact us at the address above or visit our web site.

www.istreamfs.com

Copyright© 2008 iStream Financial Services & Pertech Resources, Inc. All Rights Reserved. Patents pending. All trademarks or registered trademarks are the property of their respective owners. Printed in U.S.A. Product specifications are subject to change.

